

| Animal info  |                              |                                  |                      |               |
|--|------------------------------|----------------------------------|----------------------|---------------|
|  |                              | Light (<1.8 kg)                  | Medium (1.8–3 kg)    | Heavy (>3 kg) |
| Number of birds/pan (*)  |                              | 82–100                           | 55–82                | 40–55         |
| Density birds/m <sup>2</sup> (**)  |                              | 21–24                            | 13–21                | 10–13         |
| Max. daily feed intake (g/bird)  |                              | 170                              | 190                  | 220           |
| General & Technical info   |                              |                                  |                      |               |
|  |                              | 14 struts + shallow pan          | 10 struts + deep pan |               |
| Grill  | Struts                       | 14                               | 10                   |               |
|  | Opening between struts       | 71 mm                            | 101 mm               |               |
| Pan  | Material                     | polypropylene (support in nylon) |                      |               |
|  | Rim height (including grill) | 60 mm                            | 65 mm                |               |
|  | Diameter                     | 335 mm                           |                      |               |
| Transport  | Drive unit (***) / (****)    | 350 rpm (***) / 365 rpm (****)   |                      |               |
| Transport capacity   |                              | 450 kg/h                         |                      |               |
| Outside diameter of tubes  |                              | 44.5 mm                          |                      |               |
| Max. length per fill point   |                              | 150 m                            |                      |               |
| Suspension   |                              | max. every 3 m                   |                      |               |
| <p>(*) based on 6.6 mm/kg and circumference of Minimax is 998 mm<br/>           (**) based on 39 kg/m<sup>2</sup><br/>           (***) based on 50 Hz<br/>           (****) based on 60 Hz</p> |                              |                                  |                      |               |